

TT 043 A

TECHNICAL CHARACTERISTICS OF RUBBER COATED FABRIC

	Unit	Norm	Value	Tolerance
Weight	g/sqmt	UNI EN ISO 2286-2	3680	+/- 370
Gauge	mm	UNI EN ISO 2286-3	3.20	+/- 0.35
Tensile strength warp & weft	N/5cm	UNI EN ISO 1421	10000 / 10000	+/- 1000
Tear strength warp/weft	N	UNI EN ISO 4674-1 met. B	≥1300 / ≥1100	
Elongation	%	UNI EN ISO 1421	>20%.	
Coating fabric/adhesion	N/5cm		≥250	
Taber abrasion (weight 1000 gr – wheels H-22, flow 70, cycles 500)	Mg	ISO 5470	<150 mg	
Working temperature	°C	UNI EN ISO 2286-2	-20 +100	
Type of finishing			Fabric impression	
State of delivery			cured	

CHARACTERISTICS OF TEXTILE REINFORCEMENT

	Unit	Value
Type of yarn		PA
Weight	g/sqmt	700
Construction	dtex	1800 15 x 15

CHARACTERISTICS OF COATING ELASTOMER

Type of polymer	CR
Colour	black

APPLICATIONS

Membranes-lifting bags-hovercrafts skirts- oil booms

PROVISIONAL DATA SHEET

Novurania declines any responsibility for any damage or problem coming from a wrong usage of the product.

Issuing date 22th of April 2015

Revision: 0

I0160-0 form schede tecniche Novurania

2 di 2