

# ***TT 1006 B***

5165054

## **TECHNICAL CHARACTERISTICS OF RUBBER COATED FABRIC**

	Unit	Norm	Value	Tolerance
<b>Weight</b>	<b>g/sqmt</b>	UNI EN ISO 2286-2	<b>175</b>	<b>+/- 15</b>
<b>Gauge</b>	<b>mm</b>	UNI EN ISO 2286-3	<b>0,20</b>	<b>+/- 0,05</b>
<b>Coating adhesion</b>	<b>N/5cm</b>	Int. Novurania 10396	<b>≥ 75</b>	
<b>Working temperature</b>	<b>°C</b>		<b>-20 +80</b>	
<b>Ozone resistance</b>				<b>resistant</b>
<b>State of delivery</b>				<b>cured</b>

## **CHARACTERISTICS OF TEXTILES REINFORCEMENT**

	Unit	Value
<b>Type of yarn</b>		<b>PES</b>
<b>Weight</b>	<b>g/sqmt</b>	<b>95</b>
<b>Construction</b>	<b>dtex</b>	<b>280 18 x 17</b>

## **CHARACTERISTICS OF COATING ELASTOMER**

<b>Type of elastomer</b>	<b>CSM</b>
<b>Colour</b>	<b>black</b>